

BANDIT INTIMIDATOR 19XPC

19" Drum-Style Brush Chipper — Equipment Specification Sheet

Factory build sheet, September 2021 order (2022 model year) · Model MODEL-19XPC

ENGINE	CAPACITY	AXLE	BUILD
Ford 6.2L gas, 165 HP	19" drum style	12,000 lb, electric brakes	Under 10,000 lbs GVW

ENGINE, DRIVE & CONFIGURATION

Engine	Ford 6.2L, 165 HP gasoline engine with spark arrestor muffler (factory 3-year / 3,500-hour engine warranty from new)	990-RC1172-753
Controls	Murphy PV380 panel with reversing auto feed; 1,000 CCA battery in aluminum battery box; panel mounted on engine shroud with lockable steel cover	915-6000-39
Clutch	NACD over-center double plate clutch	700-1000-13
Drive system	Standard 19XPC drive system	990-1018-11
Winch	Dinamic winch with line docking station and electronic joystick feed assist; 5/16" x 200' Teufelberger rope with 12" loop; manual rear stabilizer	OPTION-980-5000-94
Infeed	33 1/2" high x 64" wide tapered heavy-duty infeed with weld-on pan and infeed deflectors	OPTION-925-5000-30
Feed system	Spring-loaded tool-less trap door	OPTION-915-5000-47
Axle	Single 12,000 lb leaf-spring axle with electric brakes	990-100468
Tires / rims	(2) 235/75R 17.5" tires on 8-bolt aluminum rims	OPTION-937-5000-43
Fenders	Aluminum bolt-on fenders (approx. 1/4" thick)	990-100415
Hitch	2-1/2" Wallace Forge pintle hitch	990-100274
Paint	Imron Industrial Urethane — Alert Orange	333-23662

FACTORY ADD-ON OPTIONS

• Aluminum bolt-on chock holders	OPTION-980-1000-27
• Hoop-style cone holder (bolt on)	OPTION-911-2001-42
• Documented machine weight	OPTION-911-5001-11
• 12" longer stationary tongue (tongue length 45 1/2" short frame / 49 3/4" long frame)	OPTION-911-5000-56
• 7-prong (flat / RV style) to 6-prong coiled cord adapter	OPTION-905-5000-15

STANDARD EQUIPMENT

- 37" diameter x 22" wide drum with (4) 5/8" x 5 1/2" x 10" dual edge knives
- Drum shear bar spanning the full width of the drum, mounted in the upper drum housing — creates a slicing action on a winch line or climber's rope
- Patented 'power slot' maximizing chip velocity; lets fine material escape the belly of the drum
- 30 gallon steel fuel tank with magnetic drain plug, lockable filler cap, and aluminum sight gauge
- 30 gallon steel hydraulic tank with magnetic drain plug, lockable filler cap, and aluminum sight gauge
- 360 degree hand-crank swivel discharge (height adjustable) with 12" adjustable chip deflector

- Slide box feed system (2 adjustable springs) with 2 horizontal feed wheels — top wheel 15 3/4" dia. x 24 1/2" wide, bottom wheel 10 5/8" dia. x 24 1/2" wide, each driven by a 63.9 CID motor
- Round control bar around top and sides of infeed hopper with 3 positions (forward / stop / reverse)
- Hydraulic lift cylinder for raise / down-pressure on the top feed wheel
- (2) last-chance safety pull cables
- Wooden pusher tool with mount on infeed hopper
- Clean out and inspection door on discharge bottom
- 3/16" x 2" x 6" rectangular tubing frame with 3/8" x 3" x 6" tubular tongue
- Frame / fender supports
- Lockable aluminum toolbox
- 3/8" (G70) safety chains with spring loaded latch hooks
- 8,000 lb capacity tongue jack with 15" of travel and foot pad
- 12 volt system: rubber-mounted LED taillights, 6-prong replaceable coiled power cord, protected heavy-duty wiring with junction box, LED clearance lights with reflectors
- Banded chipper drive belts (adjustable via sliding engine system)
- Weather resistant manual container; weatherproof machine, engine, and clutch manuals
- Engine disable plug for hood locking pin — engine will not run without pin in place
- Spanish & English combination safety decals
- Hydraulic pressure check kit

Offered for sale by Monster Tree Service of Foxboro, MA · (401) 480-4600

Specifications from the original factory order. Contact for condition details, service history, and viewing.